



# A method of improving the efficiency of axial-piston hydraulic motors

**A method of improving the energy efficiency of a hydraulic motor by rotating a valve cam for variable piston stroke**

**IP Status: US Patent Pending; Application number 18/243,213**

## Applications

- This technology may be applied to axial piston variable displacement pumps/motors in general if cam-based distributor valves are used instead of valve plates.
- In particular, the hydraulic motor in a line of inline hydromechanical transmissions (iHMT) - known as Hondamatic, is a viable application.
- The original Hondamatic was utilized in ATVs but similar designs are feasible in a wider range of applications, including on-road vehicles.
- The invention may also be applied to standalone variable-displacement hydraulic motors to improve power efficiency in any existing application.

## Key Benefits & Differentiators

- **Simpler**
- **More precise**
- **More compact**
- **Significantly less expensive to implement**

## Technology Overview

A typical axial-piston hydraulic motor with an adjustable swashplate and fixed valve timing cannot achieve ideal precompression and decompression across a range of operating conditions. This results in a loss in energy leading to a loss in efficiency for hydraulic motors used in All Terrain Vehicles and on-road vehicles.

Researchers at the University of Minnesota have developed a method of improving the motor's energy efficiency by rotating a valve cam for variable piston stroke. This allows, for each desired effective displacement of the hydraulic motor, a set of ideal valve timing to achieve perfect precompression and decompression so as to eliminate associated throttling losses. This technology may be applied to axial piston variable displacement pumps/motors in general if cam-based distributor valves are used instead of valve plates. In particular, the hydraulic motor in a line of inline hydromechanical transmissions (iHMT) - known as Hondamatic, is a viable application due to the existing use of cam-based distributor valves for valve timing. This technology has been demonstrated to improve the motor's efficiency in the iHMT by 5%+.

## Phase of Development

**TRL: 3-4 Scaled prototype showed efficiency improvement of 5%+**

## Desired Partnerships

This technology is now available for:

## Technology ID

2023-001

## Category

Engineering & Physical  
Sciences/Design Specifications  
Engineering & Physical  
Sciences/Energy  
Engineering & Physical  
Sciences/Transportation

## View online page



- License
- Sponsored research
- Co-development

Please contact our office to share your business’ needs and learn more.

Researchers

- [Perry Y. Li](#) Professor, Department of Mechanical Engineering

Licensing Terms

MN-IP Try and Buy
Center for Compact and Efficient Fluid Power (CCEFP) Try and Buy – Available to <a href="#">CCEFP member companies</a>
<p><b>Try</b></p> <ul style="list-style-type: none"> <li>• Trial period is up to 12 months</li> <li>• Trial fee is \$0; In place of Try fee, a business plan for the Try period is required</li> <li>• No US patent fees during Try period<sup>1</sup></li> </ul>
<p><b>Buy</b></p> <ul style="list-style-type: none"> <li>• In place of a conversion fee, a post-Try period business plan is required<sup>2</sup></li> <li>• First \$1M cumulative sales are royalty-free</li> <li>• Sublicense freely</li> <li>• Royalty rate: 2% of Net Sales</li> <li>• Patent(s) expenses paid by licensee</li> <li>• Qualified startups: 5% of equity of startup is allocated to University at formation<sup>3</sup></li> <li>• Transfer fee for transferring license to a third party - \$25,000</li> </ul>
Please contact us for detailed term sheet for a Try & Buy agreement as well as guidelines for Try <sup>1</sup> and post-Try period <sup>2</sup> business plans as well as qualified startups <sup>3</sup>

References

1. Evan D. Sand, Perry Y. Li , Incorporating A Rotatable Valve Cam To Improve The Efficiency Of A Hydraulic Motor In An Inline Hydro-Mechanical Transmission (I-Hmt), Proceedings of 2022 Bath/ASME Symposium on Fluid Power and Motion Control