A method of improving the efficiency of axial-piston hydraulic motors

A method of improving the energy efficiency of a hydraulic motor by rotating a valve cam for variable piston stroke

IP Status: US Patent Pending; Application number 18/243,213

Applications

- This technology may be applied to axial piston variable displacement pumps/motors in general if cam-based distributor valves are used instead of valve plates.
- In particular, the hydraulic motor in a line of inline hydromechanical transmissions (iHMT) known as Hondamatic, is a viable application.
- The original Hondamatic was utilized in ATVs but similar designs are feasible in a wider range of applications, including on-road vehicles.
- The invention may also be applied to standalone variable-displacement hydraulic motors to improve power efficiency in any existing application.

Key Benefits & Differentiators

- Simpler
- More precise
- More compact
- Significantly less expensive to implement

Technology Overview

A typical axial-piston hydraulic motor with an adjustable swashplate and fixed valve timing cannot achieve ideal precompression and decompression across a range of operating conditions. This results in a loss in energy leading to a loss in efficiency for hydraulic motors used in All Terrain Vehicles and on-road vehicles.

Researchers at the University of Minnesota have developed a method of improving the motor's energy efficiency by rotating a valve cam for variable piston stroke. This allows, for each desired effective displacement of the hydraulic motor, a set of ideal valve timing to achieve perfect precompression and decompression so as to eliminate associated throttling losses. This technology may be applied to axial piston variable displacement pumps/motors in general if cam-based distributor valves are used instead of valve plates. In particular, the hydraulic motor in a line of inline hydromechanical transmissions (iHMT) - known as Hondamatic, is a viable application due to the existing use of cam-based distributor valves for valve timing. This technology has been demonstrated to improve the motor's efficiency in the iHMT by 5%+.

Phase of Development

TRL: 3-4 Scaled prototype showed efficiency improvement of 5%+

Desired Partnerships

This technology is now available for:

Technology ID

2023-001

Category

Engineering & Physical
Sciences/Design Specifications
Engineering & Physical
Sciences/Energy
Engineering & Physical
Sciences/Transportation

View online



- License
- Sponsored research
- Co-development

Please contact our office to share your business' needs and learn more.

Researchers

• Perry Y. Li Professor, Department of Mechanical Engineering

Licensing Terms

MN-IP Try and Buy

Center for Compact and Efficient Fluid Power (CCEFP) Try and Buy - Available to CCEFP

member companies

Try

- Trial period is up to 12 months
- Trial fee is \$0; In place of Try fee, a business plan for the Try period is required
- No US patent fees during Try period¹

Buy

- In place of a conversion fee, a post-Try period business plan is required²
- First \$1M cumulative sales are royalty-free
- Sublicense freely
- Royalty rate: 2% of Net Sales
- Patent(s) expenses paid by licensee
- Qualified startups: 5% of equity of startup is allocated to University at formation³
- Transfer fee for transferring license to a third party \$25,000

Please contact us for detailed term sheet for a Try & Buy agreement as well as guidelines for Try 1 and post-Try period 2 business plans as well as qualified startups 3

References

 Evan D. Sand, Perry Y. Li, Incorporating A Rotatable Valve Cam To Improve The Efficiency Of A Hydraulic Motor In An Inline Hydro-Mechanical Transmission (I-Hmt), Proceedings of 2022 Bath/ASME Symposium on Fluid Power and Motion Control