



# Bio-based Elastomers from Recoverable Methyl Valerolactone (20160418, Dr. Marc Hillmyer)

**IP Status:** Issued US Patent; **Application #:** 15/712,997

## Tunable Crosslinked Elastomers with Low Glass Transition Temperature

A novel method synthesizes low-cost, polymeric valerolactones with tunable mechanical properties and low glass transition temperatures. Chemically crosslinked poly( $\beta$ -methyl- $\delta$ -valerolactone) (PMVL) elastomers are created from high molar mass PMVL homopolymers that can be chemically converted back to recover the monomer in high purity. In addition, the crosslinked PMVL materials are highly tunable and exhibit lower glass transition temperature values (near  $-50^{\circ}\text{C}$ ).

### MN-IP Try and Buy

#### Try

- \$5000 for a six month trial
- Trial fee is waived for MN companies or if sponsoring \$50,000+ research with the University
- No US patent costs during trial

#### Buy

- \$25,000 conversion fee (TRY to BUY)
- Royalty rate of 3% (2% for MN company)
- Royalty free for first \$1M in sales

## Alternative to Petroleum Based Polyurethane

Currently available bioderived and/or elastomers based on recoverable monomers are not easily tunable, exhibit poor mechanical properties, and exhibit glass transition temperature values above  $-40^{\circ}\text{C}$ , greatly limiting their applications. Commercial petroleum-derived polyurethanes are highly resistant to degradation and are environmentally unfriendly. Using recoverable aliphatic polyesters to produce thermoplastic elastomers requires rigorous reaction conditions and yields materials with poor solvent resistance, low thermal stability, and significant stress softening (Mullins effect). This method overcomes these obstacles by combining a MVL monomer and crosslinking methods. The low glass transition temperature allows these polymers to be used at lower temperatures than other biodegradable polymers and could be used in tires, gaskets, seals adhesive, sealant and damping products.

### BENEFITS AND FEATURES:

### Technology ID

20160418

### Category

Engineering & Physical  
Sciences/Materials

Engineering & Physical  
Sciences/Sustainable Technology

### Learn more



- Chemically crosslinked PMVL elastomers
- Easily biodegradable; can be chemically converted back to monomer
- Tunable mechanical properties
- Lower glass transition temperature; suitable for cold conditions
- Fillers can be added to increase toughness and reduce elastomer cost

#### **APPLICATIONS:**

- Biodegradable/biobased materials
- Polyurethanes
- Elastomers
- Damping products for vibration and noise control
- Multiple industries (e.g., bedding/furniture, building/construction, automotive/tire, footwear, transportation, and packaging)
- Flexible foams (high resilience foam seating, microcellular foam seals and gaskets)
- Low-temperature sealant and adhesive applications

**Phase of Development** - Proof of concept; demonstrated on laboratory scale. Have made a variety of polymers at two different processing temperatures; have also made composites with up to 30 wt% fumed silica.

#### **Researchers**

Marc Hillmyer, PhD

*Professor, Department of Chemistry, College of Science and Engineering*

[External Link](http://chem.umn.edu) (chem.umn.edu)

#### **Publications**

[\*Renewable, Degradable, and Chemically Recyclable Cross-Linked Elastomers\*](#)

*Industrial & Engineering Chemistry Research*, October 11, 2016 , 55 (42), pp 11097–11106