# Nanowire Based Split Ring Resonator

IP Status: Issued US Patent; Application #: 15/482,409

#### **Split Ring Resonator Using Displacement Current**

A nanowire based single ring resonator (SRR) bio microsensor significantly enhances quality factor (Q-factor) and sensitivity. The proposed nanowire-based SRR employs a displacement current that flows through nano dielectric gaps between metallic nanowires of the SRR, resulting in minimized dissipative heating and eddy current generation as well as maximized energy storage. Small gaps in the SRR act as multiple sites for chemical or biomolecule detection, and the new technology does not require tagging molecules to detect them. In addition, the SRR emits low ionizing energy (less harmful than x-rays) and does not require E-beam lithography.

#### **MN-IP Try and Buy**

#### Try

- Trial period is up to 12 months
- Trial fee is \$5000 for six months
- Trial fee is waived for MN companies or if sponsoring \$50,000+ research with the University
- No US patent expenses during trial period

## Buy

- \$100,000 conversion fee (TRY to BUY)
- Royalty rate of 3% (2% for MN company)
- Royalty free for first \$1M in sales

# **Technology ID**

20160144

## Category

Engineering & Physical Sciences/Instrumentation, Sensors & Controls Engineering & Physical Sciences/Materials Engineering & Physical Sciences/Nanotechnology

#### View online



# **Enhanced Q-factor, sensitivity and tunability**

Single ring resonators (SRRs) are artificially produced metamaterial structures with properties of electromagnetic wave manipulation not found in nature. However, conventional thin film SRRs have a low quality factor (Q-factor), low sensitivity and low frequency shift, which limit their function as sensors. Current methods to enhance the Q-factor still don't meet the needs of ultra-sensitive biosensors. The proposed nanowire-based SRR demonstrates broad range tunability, roughly a 20-fold increase in sensitivity and about a 30-fold Q-factor increase.

#### **BENEFITS AND FEATURES:**

- Enhanced sensitivity/resolution (frequency shift 20x better than thin film SRRs)
- Increased Q-factor expected: 30x better than conventional thin film SRRs
- Low ionizing energy is less harmful than x-ray for imaging applications
- Small gaps in SRR act as multiple sites for chemical or biomolecule detection
- Does not require tagging molecules or electron-beam lithography

#### **APPLICATIONS:**

- Nanobiosensors
- Low ionizing radiation imaging
- Portable, "lab on a chip" sensors to detect specific chemicals
- Biological and biomedical sensing

**Phase of Development -** Prototype Development. Early stage. Nanopillar (nanowire) based SRRs have been characterized, fabricated, and tested and correspond well between simulations and experimental data.

#### Researchers

Jeong-Hyun Cho, PhD

Assistant Professor, Department of Electrical and Computer Engineering

External Link (ece.umn.edu)

Chao Liu

Research Assistant, Department of Electrical and Computer Engineering

## **Publications**

<u>Displacement Current Mediated Resonances in Terahertz Metamaterials</u>

Advanced Optical Materials, Volume 4, Issue 8, August 2016, Pages 1302–1309

#### **External Links**

Try & Buy Term Sheet